



Fahrenheit 302/Push-on

HIGH TEMPERATURE FIRE RESISTANT MSHA COVER



Application

High Temperature, low pressure hose for hydraulic applications suitable for passage of mineral and vegetable oils, water-based solutions, water air and inert gases. Push-On hose can be used with Push-On fittings but is not recommended in vibrating or critical application.

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
FHTPUON-06-04	06	-4	6,4	1/4"	12,5	0.49	21	304	84	1216	75	3.00	0,11	0.07
FHTPUON-10-06	10	-6	9,5	3/8"	15,6	0.61	21	304	84	1216	75	3.00	0,15	0.10
FHTPUON-12-08	12	-8	12,7	1/2"	19,1	0.75	21	304	84	1216	125	5.00	0,22	0.14
FHTPUON-16-10	16	-10	15,9	5/8"	22,6	0.89	21	304	84	1216	150	6.00	0,26	0.17
FHTPUON-19-12	19	-12	19,0	3/4"	26,1	1.03	21	304	84	1216	175	7.00	0,31	0.20
FHTPUON-25-16	25	-16	25,4	1"	33	1.30	21	304	84	1216	200	8.00	0,44	0.29

Construction:
Tube: Black synthetic rubber resistant to oils
Reinforcement: one high resistant fiber braid
Cover: black, synthetic rubber resistant to oils, abrasion and weather condition

Temperature:
 -40°C to 150°C
 -40°F to 302°F

MSHA flame resistant cover
Color available: Black, Blue