



# Fighter R17

EXCEEDS SAE 100 R17



## Application

Compact hose for medium pressure application with extreme flexibility.  
Meet SAE 100R17 performance.  
Suitable for passage of mineral and vegetable oils, water-based solutions, water air and inert gases.

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
FGT17-06-04	06	-4	6,4	1/4"	12,3	0,48	225	3250	900	13000	38	1,50	0,19	0,13
FGT17-08-05	08	-5	7,9	5/16"	14,0	0,55	225	3250	900	13000	45	1,77	0,23	0,15
FGT17-10-06	10	-6	9,5	3/8"	15,9	0,63	225	3250	900	13000	50	1,97	0,29	0,19
FGT17-12-08	12	-8	12,7	1/2"	19,1	0,75	225	3250	900	13000	71	2,80	0,38	0,26
FGT17-16-10	16	-10	15,9	5/8"	23,9	0,94	225	3250	900	13000	71	2,80	0,65	0,44
FGT17-19-12	19	-12	19	3/4"	28,0	1,10	225	3250	900	13000	95	3,74	0,82	0,55
FGT17-25-16	25	-16	25,4	1"	35,3	1,39	225	3250	900	13000	114	4,49	1,16	0,78

**Construction:**  
**Tube:** Black synthetic rubber resistant to oils  
**Reinforcement:** One high tensile steel braid up to -8, two braids from -10 to -16  
**Cover:** Black, synthetic rubber resistant to oils, abrasion and weather condition

**Temperature:**  
 -40°C to 100°C (125°C discontinuous)  
 -40°F to 212°F (257°F discontinuous)

**Version available:**  
 MSHA COVER  
 MSHA HARC COVER  
 MSHA ENDLESS COVER  
 HARC COVER  
 ENDLESS COVER