



# Hot Water 600 Thin cover



## Application

Very High pressure, compact hose for cleaners. Exceeding performance required by EN 1829-2.  
Safety factor 3:1

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
600K-06-04	06	-4	6,4	1/4"	13,2	0.52	600	8700	1800	26100	100	3.93	0,32	0.22
600K-08-05	08	-5	7,9	5/16"	14,9	0.58	600	8700	1800	26100	110	4.33	0,35	0.24
600K-10-06	10	-6	9,5	3/8"	16,6	0.65	600	8700	1800	26100	120	4.72	0,4	0.27
600K-12-08	12	-8	12,7	1/2"	20,3	0.80	600	8700	1800	26100	160	6.29	0,6	0.40

**Construction:**  
**Tube:** Black synthetic rubber  
**Reinforcement:** Two high tensile steel braids  
**Cover:** Black or blue, synthetic rubber resistant to abrasion and weather condition

**Temperature:**  
 -40°C to 150°C  
 -40°F to 302°F