



Ice Fighter 2SC/R16

LOW TEMPERATURE EXCEEDS SAE 100 R16 - EN 857 2SC



Application

Low temperature compact hose with very high pressure application with extreme flexibility. Recommend for using in frigid environments on construction equipment, machine tools and agriculture application where a tighter bend radius is needed. Meet and exceed SAE 100R16 / EN 857 2SC performance. Suitable for passage of mineral and vegetable oils, water-based solutions, water air and inert gases.

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
ICF2C-06-04	06	-4	6,4	1/4"	13,2	0.52	420	6100	1680	24400	45	1.77	0,30	0.20
ICF2C-08-05	08	-5	7,9	5/16"	15,0	0.59	380	5500	1520	22000	55	2.17	0,35	0.24
ICF2C-10-06	10	-6	9,5	3/8"	16,7	0.65	350	5100	1400	20400	65	2.56	0,40	0.27
ICF2C-12-08	12	-8	12,7	1/2"	20,2	0.79	310	4500	1240	18000	80	3.15	0,55	0.37
ICF2C-16-10	16	-10	15,9	5/8"	24,0	0.94	280	4100	1120	16400	90	3.54	0,60	0.40
ICF2C-19-12	19	-12	19,0	3/4"	27,7	1.09	240	3500	960	14000	120	4.72	0,80	0.54
ICF2C-25-16	25	-16	25,4	1"	35,1	1.38	185	2700	740	10800	150	5.91	1,15	0.77
ICF2C-31-20	31	-20	31,8	1.1/4"	43,6	1.72	165	2400	660	9600	210	8.27	1,70	1.14
ICF2C-38-24	38	-24	38,1	1.1/2"	49,6	1.95	135	2000	540	8000	250	9.84	1,95	1.31

Construction:
Tube: Black synthetic rubber resistant to oils
Reinforcement: Two high tensile steel braids
Cover: Black, synthetic rubber resistant to oils, abrasion and weather condition

Temperature:
 -57°C to 100°C (125°C discontinuous)
 -70°F to 212°F (257°F discontinuous)

Version available:
 MSHA HARC COVER

DIESE RUBBER HOSES S.p.A.

Via Provinciale, 8 – SP 155 - 24040 - FILAGO (Bergamo) ITALY
 Phone: +39 (035) 49.42.300
 e-mail: diesse@diesserubber.com
www.diesserubber.com