



# Waterblast 1250 Bar

18000PSI



## Application

Very high constant pressure hose for water descaling system. Suitable for passage of water, water-soap, emulsion.

Safety factor 1:2,5

	HOSE I.D.				HOSE O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/m	lbs/ft
WB1250-06-04	6	-04	6.4	1/4"	17,3	0.68	1250	18000	3125	45000	200	7.87	0,68	0.46
WB1250-10-06	10	-06	9.5	3/8"	21,3	0.84	1250	18000	3125	45000	230	9.06	0,82	0.55
WB1250-12-08	12	-08	12.7	1/2"	25,6	1.01	1100	16000	2750	40000	230	9.06	1,13	0.76
WB1250-19-12	19	-12	19.0	3/4"	32,8	1.29	1000	14500	2500	36250	250	9.84	1,73	1.16

**Construction:**

**Tube:** Black synthetic rubber  
**Reinforcement:** Four high tensile steel spirals up to -10. Six spirals for -8  
**Cover:** black, synthetic rubber resistant to oils, abrasion and weather condition

**Temperature:**

-40°C to +90°C Operating Temperature Range  
 -10°C to +80°C Continuous Service Temperature Range  
 -40°F to 194°F Operating Temperature Range  
 +14°F to 176°F Continuous Service Temperature Range